

THE 300 GEV TRIPLET TRAIN

Andris Skuja, Ray Stefanski and Dennis Theriot

February 25, 1976

The triplet train has been augmented by three additional main ring quadrupoles to allow it to focus 300 GeV pions into enclosure 100. The triplet consists of the following elements (the additional quadrupoles are marked with asterisks):

NAME Z-positi	z-position	
0UT 3465 ft.		
OT1 (Target A) 3480 ft.		
OT2 (Target B) 3484 ft		
0QT1-1 (3Q120) 3497 ft		
0QT1-2 (3Q120) 3508 ft		
0QT2-1 (3Q84) 3522 ft		
00T2-2 (3084) 3530 ft		
00T3 (3Q84) 3541 ft		
0QT4 (3Q84) 3549 ft.		
0QT5*(3Q84) 3561 ft		
0QT6*(3Q84) 3569 ft		
0QT7 (3Q84) 3579 ft.		
00T9*(3Q84) 3619 ft.		
OVT (vertical trim) 3634 ft.		
OHT(1) (horizontal trim) 3639 ft		
OHT(2) (horizontal trim) 3642 ft.		
OHT(3) (horizontal trim) 3646 ft.		

To obtain information for the operation of the triplet train at 200 GeV or lower see TM-469. The protons are dumped at the end of the decay pipe. The 300 GeV pion beam is seperated from the primary 400 GeV proton beam by deflecting the pions 1.0 mrad to the west using the OHT trims. This creates a 3" seperation between the 400 GeV and 300 GeV beams at the end of the decay pipe. If this seperation proves to be inadequate to dump the proton beam and maintain reasonable radiation levels in Enclosure 100, OUT will have to be used to target the proton beam at an angle on to the production target.

For 300 GeV operation, the triplet train will be in the following configuration:

NAME	z-POSITION	FIELD GRADIENT	CURRENT	POWER
OTl	3480 ft	-	-	_
0QT1-1	3497 ft	4.9136 Kg/in.	104.2 A	14.5 kw
0QT1-2	3508 ft	4.9136 Kg/in.	104.2 A	14.5 kw
OQT5	3561 ft	-4.3509 Kg/in.	3172.3 A	45.3 kw
0QT6	3569 ft	-4.3509 Kg/in.	3172.3 A	45.3 kw
0QT9	3619 ft	4.5630 Kg/in.	3326.9 A	49.8 kw

Acceptance 1.4mr x 1.4 mr

Magnification at the end of the decay pipe $_{\rm X}^{\rm M}$ x $_{\rm Y}^{\rm M}$ $^{\rm M}$ 14 x 14

See Fig. 1 for the train optics and Fig. 2 for a diagram of the beam envelope.